



# ER620H

**SDLG Compact Excavator**  
**1.9t(4,188lbs) | 11.8 kW (15.8 hp)**

## Highlights

- The ER620H is equipped with a Kubota engine providing ample power for all applications.
- The width of the unit is narrow, has minimal tail swing, and great control performance providing the ideal unit for operating in confined spaces.
- Standard units offer X1/X3 pipelines, meeting a wide range of attachments.
- Auxiliary pipelines with 5 quick connectors, allow attachments to be changed quickly and efficiently.
- Full-color, high-resolution 7-inch screen that visually monitors the status of the unit.
- ROPS&TOP guard certified canopy with double rearview mirrors and three LED work lights.
- Filters are centrally located, providing easier maintenance.




**Reliability In Action**

# ER620H

## Specifications

Operating weight	kg (lbs)	1,900 (4,188)
Engine model	-	Kubota D902
Rated power	kW (hp)	11.8 (15.4)
Rated engine speed	rpm	2,300
Displacement	ml (in <sup>3</sup> )	898 (54.8)
Pump capacity	L/min (gal/min)	52 (11.4)
Main relief set pressure	bar (psi)	240 (3,480)
Max. digging force of bucket	kN (lbf)	16.5 (3,709)
Max. digging force of arm	kN (lbf)	10 (2,248)
Travel low speed	km/h (mi/h)	2 (1.2)
Travel high speed	km/h (mi/h)	4 (2.5)
Gradeability	°	30
Swing speed	r/min	9.2
Blade (width * height)	mm (in)	1,240 (48.8") * 275 (10.8")
Ground pressure	kPa (psi)	31 (4.5)
Fuel tank	L (gal)	18 (4.8)

## Dimensions



Boom length	mm (ft in)	1,830 (6')
Arm length	mm (ft in)	965 (3' 2")
Bucket capacity	m <sup>3</sup> (yd <sup>3</sup> )	0.04 (0.05)
A Max. digging reach	mm (ft in)	3,945 (12' 11.3")
B Max. digging reach on ground	mm (ft in)	3,885 (12' 9")
C Max. cutting height	mm (ft in)	3,490 (11' 5.4")
D Max. dumping height	mm (ft in)	2,435 (7' 11.9")
E Max. digging depth	mm (ft in)	2,330 (7' 7.7")
F Max. digging depth (horizontal 8 ft)	mm (ft in)	1,600 (5' 3")
G Max. vertical wall digging depth	mm (ft in)	1,770 (5' 9.7")
H Overall shipping height	mm (ft in)	2,426 (7' 11.5")
I Tail swing radius	mm (ft in)	650 (2' 1.6")
J Min. front swing radius	mm (ft in)	1,640 (5' 4.6")
K Undercarriage length	mm (ft in)	1,585 (5' 2.4")
L Overall length	mm (ft in)	3,620 (11' 10.5")
M Track width	mm (ft in)	230 (9")
W Overall shipping width	mm (ft in)	990 (3' 3")

\*SDLG reserves the right to change specifications and materials at any time without prior notification. Features of the machine in photos may include additional equipment. If you need more information and available options, please contact your local distributor or SDLG.



Congratulations SDLG for winning EFQM Global Excellence Award, one of the top three quality awards in the world.

SDLG is a leading international manufacturer of construction machinery, and the national-level high-tech company, with a wide network of dealerships and service workshops throughout the world.

## SDLG Europe B.V.

Head Office: Kelvinstraat 4 Harderwijk Netherlands  
Website: [www.sdlg.com](http://www.sdlg.com) Email: [info@sdlgeu.com](mailto:info@sdlgeu.com)