



E620H

SDLG Compact Excavator
2.2 t (4,927 lbs) | 14.6 kW (19.6 hp)

● Highlights

- The E620H is equipped with a Yanmar engine providing ample power for all applications.
- Standard units offer X1/X3 pipelines, meeting a wide range of attachments.
- Auxiliary pipelines with 5 quick connectors, allow attachments to be changed quickly and efficiently.
- Full-color, high-resolution 7-inch screen that visually monitors the status of the unit.
- ROPS certified cab with air conditioning, double rearview mirrors, and three LED lights.
- Filters are centrally located, providing easier maintenance.




Reliability In Action

E620H

Specifications

Operating weight	kg (lbs)	2,235 (4,927 lbs)
Engine model	-	YANMAR 3TNV80F
Rated power	kW (hp)	14.6 (19.6)
Rated engine speed	rpm	2,400
Displacement	ml (in ³)	1,267 (77)
Pump capacity	L/min (gal/min)	52 (11.4)
Main relief set pressure	bar (psi)	240 (3,480)
Max. digging force of bucket	kN (lbf)	16.5 (3,709)
Max. digging force of arm	kN (lbf)	10 (2,248)
Travel low speed	km/h (mi/h)	2 (1.2)
Travel high speed	km/h (mi/h)	4 (2.5)
Gradeability	°	30
Swing speed	r/min	9.2
Blade (width * height)	mm (in)	1,240 (48.8") * 275 (10.8")
Ground pressure	kPa (psi)	35 (5)
Fuel tank	L (gal)	20 (5.3)

Dimensions



Boom length	mm (ft in)	1,830 (6')
Arm length	mm (ft in)	965 (3' 2")
Bucket capacity	m ³ (yd ³)	0.04 (0.05)
Bucket width	mm (ft in)	480 (18.9")
Overall shipping size (L * W * H)	mm (ft in)	3,805 (12' 5.8")x980 (3' 2.6")x2,500 (8' 2.4")
A Max. digging reach	mm (ft in)	3,970 (13')
B Max. digging reach on ground	mm (ft in)	3,900 (12' 9.5")
C Max. cutting height	mm (ft in)	3,500 (11' 5.8")
D Max. dumping height	mm (ft in)	2,450 (8')
E Max. digging depth	mm (ft in)	2,305 (7' 6.7")
F Max. digging depth (horizontal 8 ft)	mm (ft in)	1,575 (5' 2")
G Max. vertical wall digging depth	mm (ft in)	1,740 (5' 8.5")
I Tail swing radius	mm (ft in)	980 (3' 2.6")
J Min. front swing radius	mm (ft in)	1,650 (5' 5")
K Undercarriage length	mm (ft in)	1,585 (5' 2.4")
M Track width	mm (ft in)	230 (9")

*SDLG reserves the right to change specifications and materials at any time without prior notification. Features of the machine in photos may include additional equipment. If you need more information and available options, please contact your local distributor or SDLG.



Congratulations SDLG for winning
EFQM Global Excellence Award,
one of the top three quality awards in the world.

SDLG is a leading international manufacturer of construction machinery, and the national-level high-tech company, with a wide network of dealerships and service workshops throughout the world.

SDLG North America Corp.

Head Office: 14155 West Hardy Road Houston, TX 77060
Website: www.sdlg.com Email: info@sdlgna.com