



Reliability In Action

D26H

TRACK-TYPE DOZER

Operating weight: 25000 kg

Engine power: 203 kW



Premium & Reliable

Efficient & Energy-saving

Comfortable & Convenient

D26H

Main specifications

Main parameters		Rated engine speed (r/min)	1800	Maximum lifting height (mm)	1165
Operating weight (kg)	25000	Minimum fuel consumption, g/(kW·h)	198	Maximum cutting depth (mm)	572
Ground Pressure (kPa)	64	Maximum torque (N·m) / speed (r/min)	1280/1500	Maximum tilting height (mm)	570
Ground Clearance (mm)	400	Displacement (L)	7755	Cutting angle (°)	55
Turning Radius (mm)	4125	Emissions standard	GB20891-2007	Ripper	
Maximum gradability (°)	30	Chassis system		Total weight (kg)	2420
Maximum traction force (kN)	387	Number of track rollers (per side)	7	Maximum lifting height (mm)	665
Travelling speed(F/R) (km/h)	11/11	Number of carrier rollers (per side)	2	Maximum cutting depth (mm)	948
Overall dimension and working range		Number of track shoes (per side)	40	Departure angle (°)	20.5
Overall length (mm)	5797/7850(with rear ripper)	Working device		Working width (mm)	1136
Overall width (mm)	3595	Std. flow rate (L/min)	250	Ripper tooth gauge (mm)	/
Overall height (mm)	3425	System working pressure (Mpa)	21	Service capacities	
Track ground contact length (mm)	2945	Maximum lifting speed (m/s)	0.3	Fuel (L)	500
Track Gauge (mm)	2000	Maximum lifting force (kN)	130	Hydraulic oil (L)	140
Track Width (mm)	560	Maximum pushing force (kN)	71.2	Engine crankcase oil (L)	33
Engine		Blade		Final drive (per side) (L)	35
Engine model	BFM8-28T2	Capacity (m³)	6.8	Pivot box (per side) (L)	2.5
Engine type	In-line, 6-cylinder, water-cooled, 4-stroke	Width (mm)	3595	Cooling system (L)	40
Bore / Stroke (mm)	110/136	Height (mm)	1536	AC system refrigerant (kg)	1.4
Rated engine power (kW)	203				

*SDLG reserves the right to change specifications and materials at any time without prior notification. Features of the machine in photos may include additional equipment. If you need more information and available options, please contact your local distributor or SDLG.



Shandong Lingong Construction Machinery Co., Ltd.

Add: Lingong Industry Park, Economic Development Zone, Linyi, Shandong, P.R.China
Tel: 0086-531-66590505 Fax: 0086-531-66590505 E-mail: export@sdlg.com Website: www.sdlg.com